

BreezeBond™ Product Bulletin

for Overlays/Veneers

Features and Performance

BreezeBond™ is an adjustable viscosity, soy-based adhesive made up of water, modified soy flour, and low environmental-impact inorganic additives for overlay hot-press applications. It features the following characteristics:

- Single component adhesive
- Suitable for indoor applications
- High Solids
- Adjustable Viscosity
- Strong wet bond strength
- No detectable formaldehyde
- Competitive with current overlay adhesives in the market
- Compostable

Physical Properties

Adhesive capabilities: Average wet strength 896 psi (6.18 MPa)

Color: Light yellow to beige when wet, almost white when dry.

Viscosity: 30.2-33.6 lb_m/ft-second (40K-50K mPa-s, centipoise)

Density: 8.3 lb/gal (1.00 g/cm³), **pH:** 8.0-8.5

Solids Content: Can be provided at up to 50%

VOC Content: Less than 0.008 ppm

VHAP Content: Not Applicable

Hot Press Time: 300 sec or less @ 50 psi (1.03 MPa)

Spreader Rate: 0.5-0.7 oz/ft² (16.1–21.5 mg/cm²)

General Usage Instructions

To be stored at near room temperature (68-77 °F, 20-25 °C). Prolonged exposure to elevated temperatures (140 °F, 50 °C) can lead to partial degradation.

For maximum wet adhesion strength and higher viscosity, an additive can be mixed into the adhesive prior to application. Contact the BreezeBond™ team at Specialty Organics, Inc. for more information.

Application

- 1) Mix the adhesive to give it a homogenous consistency before application.
- 2) Apply the adhesive to the plies with your method of preference (spray, roller, rubber blade / squeegee).
- 3) Bring the aligned plies together, cold pressing may help to ensure consistent surface wetting.
- 4) Press at 248 °F (120 °C) to 284 °F (140 °C) for 5 minutes.

Storage/Shelf Life

- Expected shelf life of up to three months when stored in a sealed container at room temperature. Keep away from direct sunlight. Avoid elevated temperatures.
- Keep container tightly sealed to prevent moisture from leaving the mixture.
- After long periods of storage, stirring is recommended prior to use.

Clean-up/Disposal

- Use hot water while the adhesive residue is still wet in the container/mixer/holding tank.
- Removal of dried adhesive requires a water soak followed by a high-pressure water jet.
- This adhesive is compatible with most local sewage treatment methods, however, check with local authorities for proper waste disposal.



BreezeBond™
Specialty Organics Inc.
16276 Koala Road
Adelanto, CA 92301
www.soichem.com

Warranty, Limited Remedy and Disclaimer: Specialty Organics, Inc. warrants that our products meet the applicable product specification at the time of shipment. If the product does not meet this warranty, it is our option to replace the product or refund the purchase price. Unless an additional warranty is specifically stated, Specialty Organics, Inc. does not provide any other warranties, express or implied. The user is solely responsible for evaluating the suitability of this product and determining whether it is fit for a particular product and method of application. Limitation of Liability: Except where prohibited by law, Specialty Organics, Inc. will not be liable for any loss or damage arising from the use of our product. Protected under U.S. Patent # US 9,353,300 B2